

TC508

Commercial Analog Portable Radio

Aimed at increasing efficiency the TC508 helps businesses run smoother with instant quality communications. That means a more efficient crew with projects done right the first time. This palm size and lightweight portable radio will deliver a solid and reliable two-way performance at a very competitive price.



Highlights


- **User Friendly Design**
With its palm size design, makes it easy to hold, you can take it virtually anywhere. Weighing a mere 9.87oz you will enjoy the comfort of this radio.
- **Rugged & Reliable**
Complies with MIL-STD-810 C/D/E/F standards and is IP54 (5: Generally protected against dust; 4: Protected against the effects of light rain or minor water splashes) ensuring outstanding performance..
- **16 channels**
Up to 16 channels you can switch between using the channel selector knob.
- **CTCSS / CDCSS**
Set up workgroups / users with unique CDCSS / CTCSS to prevent unwanted conversations on the same frequency.
- **Long Battery Life**
1650mAh high capacity Li-Ion battery lasts approximately 10hrs. Enhanced by a battery save feature in standby mode, with an audio & visual alert when the battery is low.

Features

- Battery Strength Indicator
- Programmable 25 / 12.5 KHz Channel Spacing
- Monitor
- CTCSS / CDCSS
- Selectable Squelch Level
- Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Retail Hotel Farming Warehouse Education Logistics Construction Property Management



Accessories

Included

- Li-Ion Battery
- Rapid-Rate Charger
- Power Adapter
- Antenna
- Belt Clip
- Strap

Optional

See website for full list



D-Earpiece with In-Line
MIC & VOX
EHM15



Remote Speaker
Microphone
SM08M3



Programming Cable
2 Pin (USB)
PC26



Nylon Carrying Case
(Non-Swivel)(Black)
NCN001

Specifications

General	Frequency Range	VHF: 146 - 174MHz; UHF1 400-470MHz; UHF2: 450-470MHz
	Channel Capacity	16
	Channel Spacing	25 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	7.4V (rated)
	RF Power Output	VHF: 5W / 2W; UHF: 4W / 2W
	Battery	1650mAh (Li-Ion)
	Battery Life (5-5-90 Duty Cycle)	Approx. 10hrs
	Frequency Stability	± 2.5ppm
	Operating Temperature	-4° F ~ 131° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	4.44 x 2.13 x 1.34 Inches
	Weight	9.87oz
	American Military Standard (Humidity / Shock / Vibration)	MIL-STD-810 C/D/E/F
	Dust & Water Intrusion	IP54 Standard
	FCC ID	See website for full list
	Canada Industry ID	See website for full list



Your Local Dealer



EventTone Wireless
making wireless easy 855-396-5450

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All rights reserved.



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025, USA
Tel: 800-845-1230 **Fax:** 954-846-1672
http: //www.hytera.us
Stock Code: 002583.SZ

Hytera
Respond & Achieve

EN20140228A